

A SIDE RAIL SLIDER HAVING IMPROVED FLY HEIGHT CONTROL

By Inventors

5

Biao Sun and Pablo Levi

Background of the Invention

Field of the Invention:

10 The present invention relates to sliders for use with magnetic data recording and retrieval systems and more particularly to air bearings for use on such sliders.

Sub A17
Magnetic disk drives are used to store and retrieve data for digital electronic apparatuses such as computers. In Figures 1A and 1B, a magnetic disk data storage system 10 of the art is illustrated which includes a sealed enclosure 12 and a plurality of magnetic disks 14 each of which has an upper surface 16 and a lower surface 18.

15 The disks are supported for rotation by a spindle 20 of a motor 22.

An actuator 24 includes an E-block 25 having at its distal end a plurality of actuator arms 26. The actuator also includes a bearing 27 which mounts the actuator 24 pivotally within the enclosure 12 and further includes a voice coil 28 at its proximal end. The voice coil is disposed between a pair of magnets 30 which are
20 fixedly connected with respect to the enclosure 12. Generating an electrical current in the coil 28 induces a magnetic field about the coil. Interaction between the magnetic fields of the coil 28 and the magnets 30 provides a desired, controlled pivotal movement of the actuator about a pivot point 31 of the bearing 27.

09476189-010300

SUMMARY OF THE INVENTION

09476189 " 010300

The present invention provides a slider, having an improved air bearing surface, for use in a data recording and retrieval system. The slider is generally block shaped, having a leading edge, a trailing edge opposite the leading edge and first and second opposing lateral sides. The air bearing surface includes a single pad located at a corner at the trailing edge of the slider. A read element and a write element are embedded within the slider at the location of the pad. The air bearing surface also includes first and second rails which run lengthwise along a portion of each lateral side. The rails are asymmetric with respect to one another in order to compensate for the fact that there is only one pad, located at a single corner of the trailing edge.

The single pad at the trailing edge of the slider is the area of highest pressure on the air bearing surface. By having only one pad, the location of the roll axis is essentially shifted toward the pad as well as the read and write elements. Therefore, the fly height of the slider at the location of the read and write elements is less affected by roll, providing improved performance. This benefit is realized while also allowing the fullest possible use of the recording disk surface area by having the read and write elements at the edge of the slider.

By configuring the rails such that the rail located at the side opposite the pad has greater surface area than the other rail, a stable flight profile can be maintained in spite of the asymmetrical pressure profile at the trailing edge caused by the asymmetrical pad placement. Testing has revealed significant improvement (roughly an order of magnitude improvement) through use of the air bearing design of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be readily understood by the following detailed description in conjunction with the accompanying drawings, with like reference numerals designating like elements of the background art.

5 Figure 1A is a partial cross-sectional front elevation view of a magnetic data storage system;

Figure 1B is a top plan view taken along line 1B-1B of Figure 1A;

Figure 1C is a view taken from line 1C-1C of FIG. 1A, shown enlarged;

Figure 1D is a view taken from line 1D-1D of FIG. 1C, shown enlarged;


10 Figure 1E is a view taken from line 1E-1E of FIG. 1C, shown enlarged;

Figure 1F is a view similar to view 1C-1C;

Figure 2 is a perspective view of a slider of the present invention;

Figure 3 is a side cross sectional view taken from line 3-3 of FIG. 2;

15 Figure 4 is a tabular illustration of performance improvements exhibited by the present invention;

 Figure 5, is a diagram of a process for constructing a head of the present invention.

DETAILED DESCRIPTION OF THE PREFERED EMBODIMENTS

With reference to FIG. 2, the present invention is embodied in a slider generally referred to as 200 for use in a data recording and retrieval system 10 (FIGs. 1A, 1B). The slider 200 includes an air bearing surface 202 having improved fly height stability performance for reading and writing data onto a magnetic disk 14 (FIGs 1A, 1B). The air bearing surface 202 includes a base surface 204. Extending from the base surface 204 are a first rail 206, a second rail 208 and a pad 210.

With continued reference to FIG. 2, the slider has embedded therein a magneto-resistive read element 212 and a magneto-resistive write element 214. The slider 200 is generally block shaped, having a leading edge 216 and a trailing edge 218. A first lateral side 220 and a second lateral side 222 opposite the first lateral side 220 both extend from the leading edge 216 to the trailing edge 218.

09476189-010300
The leading edge of the slider 200 defines a proximal end, while the trailing edge defines the distal end. The first and second rails 206, 208 are both generally doglegged in shape, each rail having a proximal foot portion 224, 226 which turns toward the other rail. The foot portions 224, 226 define there between a channel 228 having a floor 230 and first and second laterally opposing sides walls 232, 234.

With further reference to FIG. 2, the first and second rails 206, 208 define there between a cavity 236. The cavity 236 is bounded at its proximal end by the foot portions 224, 226 of the rails 206, 208, and is bounded at its lateral sides by the inner walls of the rails 206, 208. The cavity 236 has an open distal end.

The air bearing surface 202 of the slider 200 includes a intermediate surface 238 having a height which is between that of the base surface 204 and the surface of the first and second rails 206, 208. The intermediate surface 238 extends from the

leading edge 216 to the proximal edge of the of the foot portions 224, 226 of the rails 206, 208. The intermediate surface 238 also extends to the distal end of the channel 228, forming the floor 230 of the channel. The intermediate surface 238 terminates at the distal end of the channel 228 to form a shoulder 240 where the intermediate surface drops down to the base surface 204 at the proximal end of the cavity 236. In the preferred embodiment, the intermediate surface 238 extends along the outer proximal edge of the second rail 222 tapering toward the second lateral side 222 of the slider to terminate at a point midway along the length of the second rail 208.

With reference still to FIG. 2, the pad 210 has a first level 242 having a surface at generally the same elevation as the intermediate surface 238. The first level steps up to a second level 244 which has a surface at generally the same height as the surface of the rails 206, 208. The first level 242 of the pad 210 is disposed proximal to the second level 244 of the pad 210. The second level of the pad extends generally to the trailing edge 218 of the slider 200. The read element 212 and write element are embedded within the slider 218 at the pad 210 at the trailing edge 218 of the slider 200. The read and write elements 212 and 214 extend into the slider 200 in a direction perpendicular to the air bearing surface 202 with the ends of the read and write elements 212, 214 extending to the surface of the second level 244 of the slider.

With continued reference to FIG. 2, the pad 210 is located at a corner of the air bearing surface 202 which is defined by the juncture of the trailing edge 218 and the first lateral side 220. The base surface 204 extends essentially flat and smooth from the pad 210 to the corner defined by the juncture of the trailing edge 218 and the second lateral side 222, there being no other pad located between the pad 210 and the lateral side 222.

With reference now to FIG. 3, the entire air bearing surface 202 can be considered to consist of three basic height elevations. The base surface 204 defines the first elevation and serves as a reference point for the other two elevations. As can be seen with reference to FIG. 3, the second elevation extends to a height of H2 from the base surface 204. This second elevation includes the first level portion 242 of the pad 210 and the intermediate surface 238. The third elevation rises to a height H3 from the base surface and includes the second level 244 of the pad 210 as well as the first and second rails 206, 208.

With reference again to FIG. 2, during use, the disk 14 (FIGs. 1A, and 1B) will pass in close proximity to the air bearing surface 202 causing air to flow over the air bearing surface in the direction from the leading edge 216 to the trailing edge 218. As air flows over the air bearing surface, the air flowing over the raised areas of the rails 206, 208 and the pad 210 has relatively high pressure, causing the slider 200 to fly over the disk. The cavity 236 is a low pressure area which gives the slider 200 stability in its flight. The channel 228, prevents the cavity 236 from generating too great a relative vacuum which would cause the slider to effectively stick to the disk during lift off, possibly damaging the system 10.

With continued reference to FIG. 2, the slider is affected by movement in three axes of motion. Roll is defined as movement about a longitudinal axis X, and pitch is defined as movement about a lateral axis Y. With a pivot point being the intersection of these axes. The point (not shown) at which the slider 200 attaches to the suspension 32 (FIG. 1A) is the gram load position.

As will be appreciated by those skilled in the art, moving the read and write sensors 212 and 214 to the edge of the slider increases the useful space on the disk 14 (FIG. 1) from which data can be read and written. Furthermore, it is desirable to

maintain, as much as possible, a constant fly height at the location of the read and write elements. Prior art systems having read and write elements disposed near a side of the slider have maintained stable flight by including a pad at both corners of the trailing edge. The first pad in such a system contained the read and write elements while the other pad balanced the high pressure generated by the first pad. The X or roll axis of such a slider was therefore maintained near the center of the slider. Such sliders exhibit the undesirable property that the read and write elements 212, 214 are disposed away from the X or roll axis. Therefore, as the slider rolls during flight the distance between the read and write elements and the disk varies.

10 With continued reference to FIG. 2, by moving the pad 210 to the first side 220 of the slider and by having no other pad located at the trailing edge 218 of the slider 200, the pad 210 effectively becomes closer to the pivot point. As will be appreciated by those skilled in the art, the pad 210 is the location of highest pressure on the air bearing surface 202. This can be analogized as a slider supported at the trailing edge by one stiff spring at one corner rather than by two relatively soft springs at two corners. The roll axis X is essentially shifted toward the side at which the pad 210 is located.

20 Since there is only one pad 210 located at one corner of trailing edge 218 of the slider, the rails 206, 208 are formed to be asymmetric. The second rail 208 is created to have a larger surface area than the first rail 206, thereby balancing the slider and maintaining a stable flight profile.

With reference to FIG. 4, the improved flight performance of the present invention can be more fully appreciated. Testing has revealed that the present invention greatly reduces fly height variation due to roll static attitude variation. FIG. 4 shows the percentage change in fly height per degree of roll at various test zones.

